

QCK-N-9-3

N Connectors, DC~9GHz, 3-in-1

Features:
* High Precision

Applications:
* Calibration
* Laboratory Test



Description

With the components in these kits you can make error-corrected measurements of devices supplied with N connectors from DC to 9 GHz.

Components

Part Number	Description	Frequency	Impedance	VSWR	Phase Accuracy	Inner Conductor	Outer Conductor	Size	
		(GHz)	(Ω)	(Max.)	($^{\circ}$, Max.)			(mm)	
Opens	N open	DC~9	50	-	± 0.8	Gold plated beryllium copper	Passivated stainless steel	-	
				-	-			-	
Shorts	N short			-	± 0.8			-	-
				-	-			-	
Coaxial Terminations	N termination			1.032	-			-	-
				-	-			-	
Connect Joint1				-	-	Aluminium oxide		-	
QANNC-MM ²	N male to N male adapter			1.06	-	-	Gold plated beryllium copper	Passivated stainless steel	-
QANNC-FF ²	N female to N female adapter								-
Storage Box				-	-	-	-	Aluminium	160*130*65

[1] The Combination connects the Opens, Shorts and Coaxial Terminations

[2] Equal phase adapter

How To Order

QCK-N-9-3-M 3-in-1, male, including open, short and termination.

QCK-N-9-3-F 3-in-1, female, including open, short and termination.

To order a single component, specify the part number in the first column.