

QA23

2.4mm to 3.5mm

Features:
* Low VSWR

Applications:
* Wireless
* Transmitter
* Laboratory Test
* Radar

Electrical

Frequency: DC~33GHz
VSWR: 1.15 max.
1.25 max. (right angle)
Impedance: 50Ω

Mechanical

RF Connectors: 2.4mm
3.5mm
Mating Life Cycle: 500 cycles
Outer Conductor: Passivated Stainless Steel
Dielectric: PEI
Inner Conductor: Gold Plated Beryllium Copper

Environmental


Temperature: -60~+165°C

How To Order

- QA23-MM** - 2.4mm (m) to 3.5mm (m), Outline A
- QA23-MF** - 2.4mm (m) to 3.5mm (f), Outline B
- QA23-FM** - 2.4mm (f) to 3.5mm (m), Outline C
- QA23-FF** - 2.4mm (f) to 3.5mm (f), Outline D
- QA23R-MM** - 2.4mm (m) to 3.5mm (m), right angle, Outline E
- QA23R-MF** - 2.4mm (m) to 3.5mm (f), right angle, Outline F
- QA23R-FM** - 2.4mm (f) to 3.5mm (m), right angle, Outline G
- QA23R-FF** - 2.4mm (f) to 3.5mm (f), right angle, Outline H

Customization is available upon request.

Outline Drawings



Unit: mm [in]
Tolerance: ± 0.2 mm [± 0.008 in]