

QPA-18000-22000-35-13

18~22GHz, 35dB, 13dBm

Features:

- * Small Size
- * Low Power Consumption

Applications:

- * Wireless
- * Transmitter
- * Laboratory Test

Electrical

Frequency:	18~22GHz
Gain:	35dB min.
Gain Flatness:	±1.0dB typ.
Output Power (P1dB):	13dBm min.
Noise Figure:	3dB max.
Spurious:	-60dBc max.
Harmonic:	-15dBc typ.
Input VSWR:	2.0 typ.
Output VSWR:	2.0 typ.
Voltage:	+5V DC
Current:	100mA typ.

Mechanical


Size ^{*1} :	50*30*15mm 1.969*1.181*0.591in
RF Connectors:	2.92mm Female
Power Supply Connectors:	Feed Through/Terminal Post
Housing Material:	Aluminum
Mounting:	4-Φ2.2mm through-hole
Cooling:	External Heatsink (supplied on request only)

[1] Exclude connectors.

Environmental

Operating Temperature:	-20~+50°C
Non-operating Temperature:	-40~+85°C

Outline Drawings



Unit: mm [in]

Tolerance: ±0.2mm [±0.008in]

How To Order

QPA-18000-22000-35-13

Customization is available upon request.