

# QPS5-6000-18000-R

## SP5T, 6~18GHz, Reflective

**Features:**

- \* Low Insertion Loss
- \* High Isolation

**Applications:**

- \* Wireless
- \* Transmitter
- \* Laboratory Test
- \* Radar

**Electrical**

Frequency:	6~18GHz
Insertion Loss:	3dB max.
Isolation:	60dB min.
VSWR:	2 max.
Input Power:	30dBm max.
Voltage/Current:	+5V@250mA max. -5V@50mA max.
Control:	TTL High - 1 TTL Low/NC - 0
Impedance:	50Ω


**Mechanical**

Size <sup>*1</sup> :	65*22*10.2mm 2.559*0.866*0.402in
Switching Time:	120ns max.
RF Connectors:	SMA Female
Power Supply Connectors:	Feed Through/Terminal Post
Housing Material:	Nickel plated aluminum
Mounting:	4-Φ2.7mm through-hole

[1] Exclude connectors.

**Environmental**

Operating Temperature:	-45~+85°C
Non-operating Temperature:	-55~+125°C

**Outline Drawings**


Unit: mm [in]

Tolerance: ±0.2mm [±0.008in]

**Control True Table**

E1	E2	E3	E4	E5	Connection
0	1	1	1	1	J0-J1
1	0	1	1	1	J0-J2
1	1	0	1	1	J0-J3
1	1	1	0	1	J0-J4
1	1	1	1	0	J0-J5

**How To Order**

**QPS5-6000-18000-R**

Customization is available upon request.